

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET

SALES NUMBER: AP-150 Primer/Activator

DESCRIPTION: AP-150 Primer/Activator is designed for use with EPDM rubber roofing installations to enhance the performance and bond of EPDM seam adhesive. It is recommended that seams be prepared by cleaning with SW-600 prior to use of this product. This product should be scrubbed into the EPDM surface thoroughly to remove any residual surface debris. Change applicator pads or rags frequently and cover an area in excess of the area to be seamed.

COLOR: Clear to neutral

VISCOSITY (cps): #2 @ 20 rpm=200 cps or less

DENSITY (#/GAL.): 6.14#

% SOLIDS: 10.1

FLASH POINT (F): 14 F TCC

BASE: Synthetic elastomers, resin(s) and filler(s)

SOLVENT SYSTEM: Aliphatic

CLEAN-UP SOLVENT: Mineral spirits, VMP Naptha

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

PACKAGING: 5 gallon reike fitted pails or 1 gallon F-style oblong cans (6 gal/cs)