

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET (08-18-03)

SALES NUMBER: BA-100 Neoprene Bonding Adhesive

DESCRIPTION: BA-100 Neoprene Bonding Adhesive is designed for use with EPDM rubber roofing installations to adhere EPDM membrane to wood, metal, masonry and approved roofing substrates. Recommended application instructions are printed on the container label.

COLOR: Neutral to Translucent yellow

VISCOSITY (cps): #3 @ 20 rpm=2000 cps (+-400 cps)

DENSITY (#/GAL.): 7.22#

% SOLIDS: 22 (+-2%)

FLASH POINT (F): -25F TCC

BASE: Neoprene rubber and resin(s)

SOLVENT SYSTEM: Aromatics and ketone

CLEAN-UP SOLVENT: toluene

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

PACKAGING: 55 gallon drums, 5 gallon pails or 1 gallon paint cans (4 gal/case)