

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET

- SALES NUMBER:** BA-900-W LATEX BONDING ADHESIVE
- DESCRIPTION:** Milky, white liquid used in adhering single ply EPDM sheeting to various substrates. Dries by evaporation to a translucent film.
- COLOR:** Milky, white liquid when wet. Translucent when dry.
- VISCOSITY:** Brookfield RVF #3 spindle @ 20rpm=2000-4000 cps
- PH:** 5-6
- % SOLIDS:** 50 +/- 2
- DENSITY:** 8.7# +/- .3
- FLASH POINT (F):** Not applicable
- BASE:** Synthetic latex polymers
- SOLVENT SYSTEM:** Water
- CLEAN-UP SOLVENT:** Water if cleaned immediately; scrape if dry.
- APPLICATION:** Apply only to clean, dry surfaces. Apply a thin coat of adhesive to both surfaces. For highest initial bond strength join after film becomes tacky. Initial tests indicate that adhesives may be used at temperatures as low as 40F. **DO NOT ALLOW MATERIAL TO FREEZE.**
- Alternate application:** Apply enough adhesive to roof substrate so that membrane will be coated by adhesive when rolled into it. **MEMBRANE MUST BE LAID INTO WET ADHESIVE.** Wrinkles may be brushed out while adhesive is still wet. **ON HOT DAYS, THE ADHESIVE MAY DRY TOO FAST TO USE THIS PROCEDURE.**
- COVERAGE:** 80-100 sq. ft./gallon @10 wet mls. depending on substrate.
- STORAGE:** MINIMIZE CONTACT WITH ATMOSPHERIC AIR TO PREVENT INNOCULATION WITH MICROORGANISMS . Keep covered when not in use. Protect from freezing temperatures.
- HAZARDS:** Avoid inhaling concentrated vapors. Keep material from eyes. Do Not Ingest.
- FREIGHT CLASSIFICATION:** Non-hazardous. Adhesive, roofing liquid NMFC#170060 Class 55.
- PACKAGING:** 53 gallon drums, 5 gallon plastic pails, 1 gallon, lined, tin cans