

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET

SALES NUMBER: LC-400 Black Lap Caulk (Item #6)

DESCRIPTION: LC-400 Lap Caulk is a solvent based lap caulk designed to seal and protect exposed edges of EPDM membrane lap splices.

COLOR: Black

VISCOSITY (cps): 40# .104= 40-45 sec. Seivers Rheometer

DENSITY (#/GAL.): 9.26#

% SOLIDS: 61.5

FLASH POINT (F): 81F TCC

BASE: Synthetic elastomers, resin(s) and filler(s)

SOLVENT SYSTEM: Aromatic

CLEAN-UP SOLVENT: Toluene

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

PACKAGING: 5 gallon pails, 10.5 oz.fiber caulk tubes (25 tbs/crtn)