

# CONTINENTAL RUBBER COMPANY

17902 Milburn Way  
Boca Raton, FL 33498  
800-992-9973

## TECHNICAL DATA SHEET

<b>SALES NUMBER:</b>	PS-500 Pourable 2 Part Sealant
<b>DESCRIPTION:</b>	Two component pourable filler for the sealing of roof pitch pans. Cures to a tough, rubbery material. Mix bottle of Part B reactant into the gallon can of Part A, mix thoroughly being careful to scrape edges of the can as you mix and pour into the area being sealed. Pot life is 30 minutes at 77F.
<b>COLOR:</b>	Black
<b>VISCOSITY:</b>	Part A Brookfield #6 @ 4= 100,000-200,000 cps Part B Brookfield #3@20=less than 100 cps
<b>PH:</b>	N/A
<b>% SOLIDS:</b>	100
<b>DENSITY:</b>	10.76#/gal
<b>FLASH POINT (F):</b>	Greater than 300F
<b>BASE:</b>	Urethane
<b>SOLVENT SYSTEM:</b>	none
<b>CLEAN-UP SOLVENT:</b>	Before cure, use an aromatic solvent such as toluene. After curing, material will have to be cut and abraded from surface.
<b>APPLICATION:</b>	See description
<b>HAZARDS:</b>	Reference Continental PS-500 Part A and Part B MSDS before use. Use with adequate ventilation and avoid contact with skin or eyes. MDI (Part B) may cause allergic skin reaction or respiratory sensitization in susceptible individuals. Refer to Dow Papi 27 MSDS for detailed additional information on the reactant.
<b>FREIGHT CLASSIFICATION:</b>	Roofing products NMFC#170060 Class 55
<b>PACKAGING:</b>	2 part system-gallon paint cans and (136 gr. in plastic bottle) make .91 Gallon reacted material.