

# CONTINENTAL RUBBER COMPANY

17902 Milburn Way  
Boca Raton, FL 33498  
800-992-9973

## TECHNICAL DATA SHEET

**SALES NUMBER:** SW-600 Seam Wash

**DESCRIPTION:** SW-600 seam wash is designed for use with EPDM rubber roofing installations to enhance the performance and bond of EPDM seam adhesives and primers. This product should be scrubbed into the EPDM surface thoroughly to remove surface debris. Change applicator pads frequently and cover an area in excess of the area to be seamed.

**COLOR:** Clear

**VISCOSITY (cps):** Water thin

**DENSITY (#/GAL.):** 7.23#

**% SOLIDS:** 0

**FLASH POINT (F):** 41F TCC

**BASE:** Aromatic solvent

**SOLVENT SYSTEM:** Aromatic

**CLEAN-UP SOLVENT:** N/A

**STORAGE:** May be stored outside if covered to exclude water.

**HAZARDS:** Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

**FREIGHT CLASSIFICATION:** ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

**PACKAGING:** 5 gallon reike fitted pails or 1 gallon F-style oblong cans (6 gal/cs)