

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET

SALES NUMBER: TAP-150 Tape Primer

DESCRIPTION: TAP-150 Tape Primer is designed for use with EPDM rubber roofing installations to enhance the performance and bond of EPDM seam tape. The use of **SW-600** seam cleaner prior to application of this product is recommended. This product should be scrubbed into the EPDM surface thoroughly to remove surface debris. Change applicator pads frequently and cover an area in excess of the area to be seamed. This product may also be used to prep seams when using seam adhesive in your application.

COLOR: Clear to neutral

VISCOSITY (cps): #2 @ 20 rpm=200 cps or less

DENSITY (#/GAL.): 7.23#

% SOLIDS: 4.8

FLASH POINT (F): -25F TCC

BASE: Synthetic elastomers, resin(s) and filler(s)

SOLVENT SYSTEM: Aromatics and aliphatics

CLEAN-UP SOLVENT: Mineral spirits, VMP Naptha or toluene

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

PACKAGING: 5 gallon reike fitted pails or 1 gallon F-style oblong cans (6 gal/cs)