

CONTINENTAL RUBBER COMPANY

17902 Milburn Way
Boca Raton, FL 33498
800-992-9973

TECHNICAL DATA SHEET

SALES NUMBER: WC-300 Water Cut-Off Mastic (Item #7)

DESCRIPTION: WC-300 Water Cut-Off Mastic is a solvent based caulk designed to seal and protect exposed edges of EPDM membrane from water penetration.

COLOR: Grey

VISCOSITY (cps): 40# .104= 15-20 sec./20 gms. Seivers Rheometer

DENSITY (#/GAL.): 11.0#

% SOLIDS: 86

FLASH POINT (F): 14 F TCC

BASE: Synthetic elastomers, resin(s) and filler(s)

SOLVENT SYSTEM: Aliphatic

CLEAN-UP SOLVENT: Mineral spirits, VMP naptha, kerosene

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: ADHESIVE, 3, UN1133, PGII NMFC# 170060 CLASS 55

PACKAGING: 55 gallon drums, 5 gallon pails, 10.5 oz. fiber caulk tubes (25 tbs/crtn)